

HBL1283S SERIES

Heavy Duty Bolt Lock Series



200J Dynamic Impact Resistance



800Kg Holding Force



Over 1 Million Cycles
Usage Lifespan



Power to open Manual Key





Auto-Sensing 12-24VDC



Green Energy Saving



Trigger Switch Sensor



Exit Input



Key Alarm

FEATURE

HBL1283S is a heavy duty high security electric locking mechanisms designed for door closure without using any power and in the event of power failure it opens by power switch or manual release key cylinder. The unit static force hold to 800kg. It monitors the correct door closing position sending alarm indication when not correctly align. The tampering action works to engaged the lock bolt, overcoming the possibility of bolt retraction with an alarm sounding. The device can be inter-phased with access control system to control access and egress with DSS, LSS and alarm sensors to provide high security monitoring.

ONETOP

HBL1283S SERIES

SPECS	Fail Secure	Power to Oper Opens by Pow				
	Dimension	Lock Body		L 235 x W 30 x H 52mm		
		Strike Plate		L 162 x W 30 x H 6mm		
RoHS	Weight					
	Operating Voltage	12-24VDC ±10%				
	Operating Current	12VDC – 1480mA (Rush) 250mA (Hold)		24VDC - 750mA (Rush) 150mA (Hold)		
	Holding Force	800Kg				
	Impact Energy	200J				
	Operating Conditions	Temperature		-10°C ~ 60°C		
		Humidity		0 ~ 85% (non-condensing)		
	Output Signals	Lock Status Sensor		Door Status Sensor		
		(LSS)		(DSS)		
		COM/NC/NO: Max 24VDC;		COM/NC/NO: Max 24VDC;		
		,			A;Max 6W	
	Key Alarm	COM、NO. Dry Contact Signal Output Max 24VDC; Max 200mA				
	Trigger Switch Sensor	COM、NO. Door And Lock Contact Status Output Max 24VDC; Max 1A ; Max 6W				
	Exit Input	ON Exit And Grovnd Wine, Connection Must Be Grounded				
	Face Plate	Stainless Steel Face Plate				
	Bolt	Stainless Steel Bolt				
		Lock Status Sensor Monitoring	Door Status Sensor Monitoring	Key Alarm	Trigger Switch Sensor	Exit Input
MODELS	HBL1283S	•	•	•	•	•
ACCESSORIES	CP44 YTL40/50/70/97-SK YTL70-DK	Cover Plate for European Cylinder Double Sided Key Cylinder For European Profile (40/50/70/97mm in length) Single Sided Key Cylinder With Knob European Profile (70mm in length)				