



200Kg Holding Force



Power to Open
Power to Lock



Over 1 Million Cycles
Usage Lifespan



CL0001



CL0001DM

FEATURE

Equipped with dual monitoring and interchangeable between the POWER TO LOCK (Fail Safe) mode and POWER TO OPEN (Fail Secure) mode, The cabinet lock series is designed to fit into mailbox cabinets and lockers with swing or sliding doors.

SPECS



Fail Safe/Secure	Interchangable	Power to Open	Power to Lock
Dimension	Lock Body	L 73 x W 30 x H 28.5mm (CL0001)	L 94 x W 30 x H 32mm (CL0001DM)
	Strike Plate	L 40 x W 18 x H 31mm	
Weight	0.35Kg		
Operating Voltage	12/24VDC ±10%		
Operating Current	12VDC – 200mA	24VDC – 100mA	
Holding Force	200Kg		
Operating Conditions	Temperature	-10°C ~ 60°C	
	Humidity	0 ~ 85% (non-condensing)	
Output Signals	Lock Status Sensor (LSS) Option	Door Status Sensor (DSS) Option	
	COM/NC/NO: 125VAC/1A; 30VDC/0.5A	COM/NC/NO: 125VAC/3A; 30VDC/2A	
Surface Finishes	Powder coated black		

MODELS

	Lock Status Sensor Monitoring	Door Status Sensor Monitoring
CL0001		
CL0001-12-8		
CL0001DM	•	•