



R60-PCH-LSS



R60-PCV-LSS



60Kg Holding Force



Power to Lock



Door Release bottom

FEATURE

Fire and smoke door magnetic door holder, no residual magnetism with excellent quality surface finished, Supplied in 12 or 24VDC power. The devices have to be linked to fire / smoke alarm system. When a fire alarm occurs, power is removed from the devices and the doors are returned to the closed condition, preventing the spread of fire and/or smoke to other areas.

SPECS



Fail Safe

Dimension

Weight

Operating Voltage

Operating Current

Holding Force

Operating Conditions

Output Signals

Surface Finishes

Power to Lock

Lock Body

R60-PCH-LSS

L 148 x W 90 x H 90mm

R60-PCV-LSS

L 90 x W 90 x H 107.3mm

Armature Plate

L 30.4 x W 65 x H 65mm

1.2Kg

12/24VDC ±10%

12VDC – 200mA

24VDC – 90mA

60Kg

Temperature

-10°C ~ 60°C

Humidity

0 ~ 85% (non-condensing)

Lock Status Sensor

(LSS) Option

COM/NC/NO:

Max 30VDC; Max 0.2A

High Quality Plating for Anti-corrosion

MODELS

	Lock Status Sensor Monitoring	Extension Wall Mount	Floor Mount
R60-PCH-LSS	•	•	
R60-PCV-LSS	•		•