

# ONETOP

## EM5000G/LF

Fire Rated  
Environmental Friendly  
Weather Resistant  
Electromagnetic Lock



200J Dynamic  
Impact Resistance




600Kg Holding Force



Over 1 Million Cycles  
Usage Lifespan



Power to Lock



Anti-Corrosion Plating  
Passed 96Hrs Salt Spray Test



Robust Stainless  
Construction



Front or Side Fixing  
Arrangement



Ingress Protection  
Certification

### FEATURE

The EM5000G/LF series are dual operating 12/24VDC Fail-Safe electromagnetic lock in stainless steel encase body, highly quality plated for more corrosion resistant and instantly release to unlock when powered OFF without any residual magnetism. The lock fixing arrangement can be on the front or side, for use on swing or sliding interior or exterior gate perimeter security with Lock status monitoring sensor and built-in surge protection. This new design has been tested to be fire rated for 3 hours and product has been classified to be environmental friendly.

## SPECS



### Fail Safe

#### Dimension

#### Weight

#### Operating Voltage

#### Operating Current

#### Holding Force

#### Impact Energy

#### Operating Conditions

#### Output Signals

#### Surface Finishes

#### Residual Magnetism

### Power to Lock

#### Lock Body

#### Armature Plate

#### Weight

#### Operating Voltage

#### Operating Current

#### Holding Force

#### Impact Energy

#### Temperature

#### Humidity

#### Lock Status Sensor (LSS)

#### COM/NO/NC:

#### Max 24VDC; Max 1A

#### Full weather resistant stainless Steel finish;

#### Electro galvanization to prevent from rusting

#### No residual magnetism

\*No spring rebound mechanism on armature plate is required to overcome residual magnetism

#### Lock Status Sensor Monitoring

#### Side Mount

#### Front Mount

#### Conduit Head Connector

## MODEL

### EM5000G/LF

•

•

•

•

## ACCESSORIES

### L&Z EM5000G

In-swing door L&Z bracket

### BL 5000GL

L bracket and mounting plate for Sliding Door application